

# CERTIFICATE

This is to certify that

# Nathaniel Salawu, Adamu Hussaini, Sadiq Abubakar Muhammed, Dauda Usman Suleiman, Sunday Achimugu

has contributed a paper titled

Energy Detection based Measurement and Analysis of Spectrum Occupancy for ADHOC Cognitive Network Resource for Federal University of Technology, Minna, Nigeria

in the

## NINTH INTERNATIONAL CONGRESS ON INFORMATION AND COMMUNICATION TECHNOLOGY

Organised & Managed by Global Knowledge Research Foundation & G R Scholastic LLP

The paper has also been selected for publication in the (ICICT 2024) Conference as per fulfilment of guidelines issued by Springer.



R. SIMON SHERRATT UNIVERSITY OF READING UNITED KINGDOM



XIN-SHE YANG MIDDLESEX UNIVERSITY UNITED KINGDOM



19-22 FEBRUARY, 2024 DIGITAL PLATFORM : ZOOM



NILANJAN DEY TECHNO INDIA COLLEGE OF TECHNOLOGY INDIA

AMIT JOSHI ORGANISING SECRETARY ICICT 2024







SPRINGER NATURE

# Lecture Notes in Networks and Systems 1000

1000th Volume of LNNS · 1000th Volume of LN

Xin-She Yang · Simon Sherratt · Nilanjan Dey · Amit Joshi *Editors* 

Proceedings of Ninth International Congress on Information and Communication Technology VICT 2024, London, Volume 5

Springer

## Lecture Notes in Networks and Systems

### Volume 1000

#### Series Editor

Janusz Kacprzyk, Systems Research Institute, Polish Academy of Sciences, Warsaw, Poland

#### **Advisory Editors**

Fernando Gomide, Department of Computer Engineering and Automation—DCA, School of Electrical and Computer Engineering—FEEC, University of Campinas—UNICAMP, São Paulo, Brazil

Okyay Kaynak, Department of Electrical and Electronic Engineering, Bogazici University, Istanbul, Türkiye

Derong Liu, Department of Electrical and Computer Engineering, University of Illinois at Chicago, Chicago, USA

Institute of Automation, Chinese Academy of Sciences, Beijing, China

Witold Pedrycz, Department of Electrical and Computer Engineering, University of Alberta, Alberta, Canada

Systems Research Institute, Polish Academy of Sciences, Warsaw, Poland

Marios M. Polycarpou, Department of Electrical and Computer Engineering, KIOS Research Center for Intelligent Systems and Networks, University of Cyprus, Nicosia, Cyprus

Imre J. Rudas, Óbuda University, Budapest, Hungary

Jun Wang, Department of Computer Science, City University of Hong Kong, Kowloon, Hong Kong

The series "Lecture Notes in Networks and Systems" publishes the latest developments in Networks and Systems—quickly, informally and with high quality. Original research reported in proceedings and post-proceedings represents the core of LNNS.

Volumes published in LNNS embrace all aspects and subfields of, as well as new challenges in, Networks and Systems.

The series contains proceedings and edited volumes in systems and networks, spanning the areas of Cyber-Physical Systems, Autonomous Systems, Sensor Networks, Control Systems, Energy Systems, Automotive Systems, Biological Systems, Vehicular Networking and Connected Vehicles, Aerospace Systems, Automation, Manufacturing, Smart Grids, Nonlinear Systems, Power Systems, Robotics, Social Systems, Economic Systems and other. Of particular value to both the contributors and the readership are the short publication timeframe and the world-wide distribution and exposure which enable both a wide and rapid dissemination of research output.

The series covers the theory, applications, and perspectives on the state of the art and future developments relevant to systems and networks, decision making, control, complex processes and related areas, as embedded in the fields of interdisciplinary and applied sciences, engineering, computer science, physics, economics, social, and life sciences, as well as the paradigms and methodologies behind them.

Indexed by SCOPUS, INSPEC, WTI Frankfurt eG, zbMATH, SCImago.

All books published in the series are submitted for consideration in Web of Science.

For proposals from Asia please contact Aninda Bose (aninda.bose@springer.com).

Xin-She Yang · Simon Sherratt · Nilanjan Dey · Amit Joshi Editors

# Proceedings of Ninth International Congress on Information and Communication Technology

ICICT 2024, London, Volume 5



*Editors* Xin-She Yang Middlesex University London, UK

Nilanjan Dey Techno India College of Technology Kolkata, West Bengal, India Simon Sherratt University of Reading Reading, UK

Amit Joshi Global Knowledge Research Foundation Ahmedabad, Gujarat, India

ISSN 2367-3370 ISSN 2367-3389 (electronic) Lecture Notes in Networks and Systems ISBN 978-981-97-3288-3 ISBN 978-981-97-3289-0 (eBook) https://doi.org/10.1007/978-981-97-3289-0

© The Editor(s) (if applicable) and The Author(s), under exclusive license to Springer Nature Singapore Pte Ltd. 2024

This work is subject to copyright. All rights are solely and exclusively licensed by the Publisher, whether the whole or part of the material is concerned, specifically the rights of translation, reprinting, reuse of illustrations, recitation, broadcasting, reproduction on microfilms or in any other physical way, and transmission or information storage and retrieval, electronic adaptation, computer software, or by similar or dissimilar methodology now known or hereafter developed.

The use of general descriptive names, registered names, trademarks, service marks, etc. in this publication does not imply, even in the absence of a specific statement, that such names are exempt from the relevant protective laws and regulations and therefore free for general use.

The publisher, the authors and the editors are safe to assume that the advice and information in this book are believed to be true and accurate at the date of publication. Neither the publisher nor the authors or the editors give a warranty, expressed or implied, with respect to the material contained herein or for any errors or omissions that may have been made. The publisher remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

This Springer imprint is published by the registered company Springer Nature Singapore Pte Ltd. The registered company address is: 152 Beach Road, #21-01/04 Gateway East, Singapore 189721, Singapore

If disposing of this product, please recycle the paper.

### Preface

The Ninth International Congress on Information and Communication Technology will be held during 19–22 February 2024, in a hybrid mode, physical at London, UK and digital platform Zoom. ICICT 2024 was organised by Global Knowledge Research Foundation and managed by G. R. Scholastic LLP. The associated partners were Springer and Springer Nature. The conference will provide a useful and wide platform both for display of the latest research and for exchange of research results and thoughts. The participants of the conference will be from almost every part of the world, with backgrounds of either academia or industry, allowing a real multinational and multicultural exchange of experiences and ideas.

A great pool of more than 2400 papers were received for this conference from across 129 countries among which around 485 papers were accepted and will be presented physically at London and digital platform Zoom during the four days. Due to the overwhelming response, we had to drop many papers in the hierarchy of the quality. Total 70 technical sessions will be organised in parallel in 4 days along with a few keynotes and panel discussions in hybrid mode. The conference will be involved in deep discussion and issues which will be intended to solve at global levels. New technologies will be proposed, experiences will be shared, and future solutions for design infrastructure for ICT will also be discussed. The final papers will be published in ten volumes of proceedings by Springer LNNS Series. Over the years, this congress has been organised and conceptualised with collective efforts of a large number of individuals. I would like to thank each of the committee members and the reviewers for their excellent work in reviewing the papers. Grateful acknowledgements are extended to the team of Global Knowledge Research Foundation for their valuable efforts and support.

I look forward to welcoming you to the 10th edition of this ICICT Congress 2025.

Amit Joshi, Ph.D. Organising Secretary, ICICT 2024 Director—Global Knowledge Research Foundation Ahmedabad, India

# Contents

A New Wavelet Visual Weighting Model to Optimize Image Coding and Quality Evaluation Based on the Human Psychovisual Quality Properties Ilham Morino, Abderrahim Bajit, Abdelhadi EL Allali, Rachid EL Bouayadi, and Driss Zejli	1
Optimizing the IoT PAYLOAD Encryption Watermarking-Oriented Applying Computational Intelligence and Visual Quality Coding to Improve the Vehicular Speed Controller Platform's Features Y. Onqani, Abderrahim Bajit, B. Essounaini, Abdelhadi EL Allali, H. Essamri, and Driss Zejli	17
Influence of Ethical Behavior on Job Satisfaction of Membersof Information System Project TeamEmmanuel Samuel Mtsweni	33
<b>To Be or Not To Be—After AI Revolution</b>	51
Use of Analytical Methods in Variant Forecasting Tasks V. V. Kukartsev, A. S. Borodulin, S. A. Zamolotskii, V. A. Nelyub, and A. R. Glinscaya	63
Toward a Classification of Factors Influencing eWOM in Online Shopping Through a Systematic Literature Review Nisrine Benhammou, Khaoula Zahouani, Habiba Bensassi Nour, and Youssef Makloul	71
Away from Theory: A Cloud Storage Application with Public KeySearchable Encryption FeatureMohammed Raouf Senouci, Abdelkader Senouci, Fagen Li,and Kumar K. Busawon	81

<b>Developing a Serious Game for Acute Pain Detection by Utilizing</b> <b>Virtual Reality and Brain-Computer Interfaces</b> Meisam Taheri, Adam Emile Aske, and Kevin Tan	93
Hidden Knowledge Extraction for Association Rule Mining Technique Based on the Apriori and Frequent Pattern Growth Algorithms: A Case Study Thierry Nsabimana, Therence Niyonsaba, Christian Ildegard Bimenyimana, Ghislain Vlavonou, Joël T. Hounsou, and Gerard Niyonsaba	103
Integration of Distributed Intrusion Detection Systems in IoT Infrastructure Christian Ildegard Bimenyimana, Thierry Nsabimana, Ghislain Vlavonou, Joël T. Hounsou, and Gerard Niyonsaba	115
Predictive Analysis Model to Improve the Control of EatingDisorders in Adolescents in Metropolitan Lima Based on MachineLearningJeffery Bryce Molina Solano, Valeria Angelica Castillo Revelo,and Víctor Manuel Parasi Falcon	125
A Predictive Model to Support Decision-Making for the Accreditation of Learning Programs Using Data Mining and Machine Learning Francis Kawesha and Jackson Phiri	137
Design of a Block chain-Based Organ Donation and TransplantationManagement FrameworkMurat Osmanoglu, Murat Karakus, Bulent Tugrul, and Salih Demir	155
Audio Style Transfer Using a Modified Lightweight TimbreTronPipelineAlaa Elkouni, Mohamed ElMohandes, Imran Zualkernan,and Ali Reza Sajun	165
<b>Deep Dive into Invoice Intelligence: A Benchmark Study</b> <b>of Leading Models for Automated Invoice Data Extraction</b> Merxhan Bajrami, Nevena Ackovska, Biljana Stojkoska, Petre Lameski, and Eftim Zdravevski	177
Combined ECG Analysis Approach Based on Detection of Deviation from the Personal or Population Norm Using Wearable Devices Vladyslav Malanin and Illya Chaikovsky	193

#### Contents

Atenea Lab: A Softwarized IoT Laboratory for Researchand Knowledge TransferMarta Fuentes-García, Celia Fernández, Marina Torres,Luis El-Moga-Sarria, and Francisco L. Benítez-Martínez	205
<b>Exploring the Antecedents of Purchase Intention for Organic</b> <b>and Healthy Foods: A Systematic Literature Review</b>	215
Communicating Universe Petr Klán	227
An Overview on Diagnosis of Endometriosis Disease Based on Machine Learning Methods Liviu-Andrei Scutelnicu, Radu Maftei, and Mihaela Luca	237
Blockchain-Integrated Chatbot	251
Switching from DOORS to DOORS Next Generation. Identifying the Main Usability Issues. A Case Study Oana Rotaru, Silviu Vert, and Radu Vasiu	261
A Study on Image Enhancement and Noise Filtering of Kato-Katz Images Farah Sinada, Saumya Kareem Reni, and Izzet Kale	277
Synthetic Data for Feature Selection Firuz Kamalov, Rohan Mitra, and Hana Sulieman	291
<b>RayPet: Unveiling Challenges and Solutions for Activity</b> <b>and Posture Recognition in Pets Using FMCW Mm-Wave Radar</b> Ehsan Sadeghi, Abel van Raalte, Alessandro Chiumento, and Paul Havinga	303
<b>"Slice and Dice": A Corpus-Based Study of Russian Binomials</b>	319
Design of Deep Learning-Based Intelligent Blind Direct SequenceCode Division Multiple (DS-CDMA) Access ReceiverM. N. Drakshayini and Manjunath R. Kounte	327
Nutrilac: Application for Dairy Cattle Diet Formulation	339

Contents
----------

Data Mining and Machine Learning-Based Predictive Modelto Support Decision-Making for the Accreditation of LearningProgrammes at the Higher Education AuthorityFrancis Kawesha and Jackson Phiri	351
Enquiry-Based Learning Pedagogy—Design, Development and Delivery of a Reproducible Robotics Framework Aimee Walker, Katherine Regina Vasquez Diaz, Darren McKie, and Jamshed Iqbal	363
Application of the Negative Selection Algorithm to DetectDistributed Denial of Service AttacksDaniel Matrone, Rodrigo P. Pasquale, and Calebe P. Bianchini	375
PharmaSys: Toward Preventing Prescription Misuse Using a HIPAA-Compliant Blockchain ProtocolAaron H. Nguyen, Alex Lewtschuk, James Lucas Durham, Peyton Lundquist, and Gaby G. Dagher	387
<b>Exploration and Integration Potential of ChatGPT in Civil</b> <b>Engineering: Advances, Challenges and Application Prospects</b> Israel Benjamin Luis Rivera Barreto and Yvan Huaricallo Vilca	407
A Case Study of Student Performance Predictions in English Course: The Data Mining Approach Tran Duc Quynh, Nguyen Doan Dong, and Nguyen Quang Thuan	419
Securing Bluetooth Technology in Healthcare: A Comprehensive Case Study and Practical Insights Senzo Ntsele and Khutso Lebea	431
Modeling and Simulation in Temperature Control in Milk Coagulation for Edam Cheese Production Using Fuzzy Logic Honorato Ccalli Pacco	443
AMEACrypt: Android Mobile Encryption Application GeneratingPassword Using AES AlgorithmJerry E. Borromeo, Roxanne A. Pagaduan, Junnel E. Avestro,Ryan Christopher B. Pinca, Jess N. Garcia, and Zyrus D. Gremio	455
Securing the Internet of Flying Things (IoFT): A Proficient Defense Approach Qasem Abu Al-Haija, Abdulaziz A. Alsulami, Badraddin Alturki, and Mohammad Alnabhan	469
Speaker Recognition with Deep Learning Approaches: A Review	481

Abdulrahman S. Alenizi and Khamis A. Al-Karawi

#### Contents

Social Media Emotion Detection and Analysis System UsingCutting-Edge Artificial Intelligence TechniquesTapu Rayhan, Ayesha Siddika, Mehedi Hasan, and Nafisa Sultana Elme	501
<b>Utilization of Social Media as a Community and School Relations</b> <b>Channel in Encouraging Students' Entrepreneurial Career Choices</b> Maisyaroh, Juharyanto, Maulana Amirul Adha, Nova Syafira Ariyanti, Indra Lesmana, and Anabelie Villa Valdez	515
Enhancing Healthcare User Interfaces Through Large Language Models Within the Adaptive User Interface Framework Akash Ghosh, Bo Huang, Yan Yan, and Wenjun Lin	527
Enhancing Telehealth Patient Experience with Emotion-Sensitive Large Language Models Indira Del Rosario, Akash Ghosh, Bo Huang, Yan Yan, Wenjun Zhang, and Wenjun Lin	541
<b>Different Processes for Graphical Recognition of Derivative</b> <b>of a Function: An Eye-Tracker Analysis</b> Camilla Spagnolo, Christian Casalvieri, and Alessandro Gambini	551
<b>Emails Classification: Comparing Statistics, Machine-Learning,</b> <b>Deep-Learning, and ChatGPT Prompting Techniques</b> Pablo Turón, Montse Cuadros, Alicia Grande, and David Lopez	561
Blockchain Technologies for Transparency in FinTech	575
Energy Detection-Based Measurement and Analysis of Spectrum Occupancy for Ad hoc Cognitive Network Resource for Federal University of Technology, Minna, Nigeria Nathaniel Salawu, Adamu Hussaini, Sadiq Abubakar Muhammed, Dauda Usman Suleiman, and Sunday Achimugu	587
Third-Party Data Leaks on Municipal Websites	599
Evaluating Tabular Data Generation Techniques on the DaFne Platform: Insights from a Predictive Maintenance Case Study on BridgesPramod Baddam, Ayse Glass, René Jäkel, Jonathan Jander, Tom Krause, Pamela Kunert, Järg Rainer Noennig, Iryna Okhrin, Mariela Sanchez, and Ulrike Steffens	611
Cyber Threat Hunting Using Large Language Models	629

Transforming Patient Experience in Underserved Areas	
with Innovative Voice-Based Healthcare Solutions Minliang Xia, Bo Huang, Yan Yan, Wenjun Zhang, and Wenjun Lin	643
Fortifying Machine Learning-Powered Intrusion Detection:A Defense Strategy Against Adversarial Black-Box AttacksMedha Pujari and Weiqing Sun	655
Author Index	673

## Energy Detection-Based Measurement and Analysis of Spectrum Occupancy for Ad hoc Cognitive Network Resource for Federal University of Technology, Minna, Nigeria



Nathaniel Salawu<sup>®</sup>, Adamu Hussaini<sup>®</sup>, Sadiq Abubakar Muhammed<sup>®</sup>, Dauda Usman Suleiman<sup>®</sup>, and Sunday Achimugu<sup>®</sup>

**Abstract** The rising demand for wireless communication systems has led to the exponential growth in the figure of wireless devices. As a result, there is a significant scarcity of available spectrum, which can limit the capacity and quality of wireless communication networks. Cognitive radio (CR) technology is a good solution to this challenge as it enables the most effective use of spectrum resources by permitting wireless devices to dynamically use under-utilized spectrum. This research presents a measurement of real-time spectrum sensing and detection of white space of cognitive wireless technologies for microwave and wireless communication systems of the Federal University of Technology, Minna main campus. Different spectrum sensing techniques including cyclostationary feature detection (CFD), matched filter detection (MFD) and energy detection (ED), have been widely researched. In this research, ED model for enhanced spectrum sensing-based cognitive radio technology that is capable of adapting to changing environmental conditions is adopted. Comprehensive field measurements were carried out in the study area using an 8.5 GHz BK precision 2658A spectrum analyzer (SA). Specifically, a received signal strength (RSS) of 7.3 dBm was obtained at 10 m while at a distance of 1500 m, 143.93 dBm was recorded alongside other similar results. The results were validated by comparing the standard deviation (SD) parameter, and root mean square error (RMSE) based on the adopted ED model with a reference spectrum sensing technique. Thus, the adopted ED technique is a more realistic spectrum sensing technique for microwave and mobile communication systems in the study area and similar environments.

**Keywords** Cyclostationary feature detection technique · Matched filter detection technique Energy detection technique · Cognitive radio

587

N. Salawu  $(\boxtimes) \cdot A$ . Hussaini  $\cdot S$ . A. Muhammed  $\cdot D$ . U. Suleiman  $\cdot S$ . Achimugu Telecommunications Engineering Department, Federal University of Technology, Minna, Niger State, Nigeria

e-mail: nathsalawu@futminna.edu.ng

<sup>©</sup> The Author(s), under exclusive license to Springer Nature Singapore Pte Ltd. 2024 X.-S. Yang et al. (eds.), *Proceedings of Ninth International Congress on Information and Communication Technology*, Lecture Notes in Networks and Systems 1000, https://doi.org/10.1007/978-981-97-3289-0 47

#### 1 Introduction

The rapid increase in need for quality wireless communication transmission and reception has brought a lot of challenges on the scarce radio spectrum. Consequently, some researchers claim that this challenge is the result of insufficient techniques for spectrum access [1], instead of the assumption of physical scarcity of spectrum. In recent times, some regulatory agencies have issued spectral license permits for exclusive utilization of some dedicated frequency bands. Previous works have revealed that many of the licensed radio signal spectral bands may not be efficiently put to use in space and time [2] giving rise to unused "white spaces" in the time–frequency domain at any particular area. The utilization of spectrum is largely around a certain portion of the spectrum while a large expanse of the spectrum may not be utilized as some other part as seen in Fig. 1.

As can be observed from Fig. 1, spectrum usage is more serious and competitive at frequencies lower than 3 GHz. It is also clear that the spectrum is not fully utilized around the frequency bands of 3–6 GHz. On the other side, static spectrum allocation strategies will not allow for re-utilization of the rarely used spectrum allotted to licensed users by unlicensed users. This means that the radio spectrum could be better utilized than the traditional usage. To achieve this, there is a need for a careful analysis of the spectrum occupancy to make precise recommendation on the extent of spectrum utilization. This has called for a new communication standard by which unlicensed (secondary) users to quickly access the free or vacant spaces which are reserved for licensed (primary) users in a process known as cognitive radio.



Fig. 1 Spectrum utilization measurements [2]

The knowledge behind the CR standard is the assessment of the free frequency bands assigned to the primary users (licensed users) taking the secondary users (unlicensed users) into consideration without any interference imposed on the licensed users' transmission and reception [3, 4]. Figure 2 depicts the cycle process of cognitive radio comprising four phases described as spectrum sensing phase, spectrum decision phase, followed by spectrum mobility phase and lastly, spectrum sharing phase [5]. First, in the CR spectrum sensing process, the CR categorizes the available portion of the spectrum section that can be utilized. It can also sense the PU presence when it is restored into operation in a way that guarantees an efficient track of the network. The second phase is the spectrum decision process. The CR selects the correct frequency band depending on the user's quality of service requirements (QoS) and spectrum requirement. In the third process also known as spectrum sharing, the spectrum utilization is coordinated between the SUs and PUs in a way that maintains the interference value below a certain threshold. Finally, the CR frees the channel when the PU begins to use it during the stage of spectrum mobility. This means the spectrum must be aware and update dynamically [6].

The achievement of CR largely rests on its ability to sense "spectral holes" and the backing of the regulatory bodies for granting CR permission to use licensed frequency bands is another gain. The initial stage of CR implementation is the investigation of the accessibility of the momentarily unoccupied spectral resources such as time, frequency and lastly, space. The projected technology known as dynamic spectrum access (DSA) is one of the promising possible solutions to these challenges. DSA configurations are of two types and these are the concurrent spectrum access (CSA) model and the opportunistic spectrum access (OSA) model [7]. The OSA technology allows SU to utilize the radio spectrum if only active PUs are in session. Conversely, the CSA technology also called underlay CR allows Pus and Sus to co-exist at the



**Fig. 2** Cognitive radio cycle [5]



Fig. 3 Matched filter detection technique

same time within the same geographic location area. However, the interference posed by the SUs to the PUs must be kept within an acceptable pre-determined value of threshold also known as the interference temperature limit value [8].

#### 2 Cognitive Radio Techniques

There are several techniques to sense idle spectrum channels and utilize them to increase the networks efficiency. In this study, we looked at MFD, CFD and ED.

#### 2.1 Matched Filter Detection (MFD)

Spectrum sensing based on MDF uses pilot signals values that are fixed to the primary signal value so as to sense the availability of a PU. These pilot signal values are used in transmission and reception of signals for synchronization and, typically contributes between 1 and 10% based on the total signal power value transmitted. The unidentified primary signal value is convolved along time reversed form of the pilot signal. Assuming the model signal is present in the unidentified signal wave, then the PU is taken to be present, or it is otherwise taken to be absent. The system block diagram of an MFD-based spectrum sensing technology is presented in Fig. 3 and the mathematical model is described in Eq. (1)

$$Y[n] = \sum_{k=-\infty}^{\infty} h[n-k]y[k]$$
(1)

#### 2.2 Cyclostationary Feature Detection (CFD)

CFD exploits statistical characteristics assigned to the primary signal so as to find the availability/absence of primary users with the aid of spectral correlation. Equation (2) presents the equation for implementing CFD while Fig. 4 depicts its block diagram.



Fig. 4 Cyclostationary feature detection technique

$$r_{y}[n,\tau] = \mathbb{E}[y[n]y * [n+\tau]]$$
<sup>(2)</sup>

#### 2.3 Energy Detection (ED)

ED spectrum sharing technique is based on non-coherent detection scheme that determines the energy level of the received signal. It compares it with an established threshold value that is based on the level of noise flood [9]. In ED-based spectrum sensing utilization, the received signal obtained is filtered around the bandwidth concerned and squared. The signal is later integrated over a specified observation interval value. This ensures that the measure of the received signal's energy level is compared with the detection threshold [10, 11]. Figure 5 shows the detailed block diagram of ED-based spectrum sensing utilization while Eq. (3) presents its mathematical relationship.

$$y(n) = x(n) + w(n) \tag{3}$$

The main criteria for spectrum sensing is function of signal detection in a negative signal-to-noise-ratio (SNR). Owing to the dynamic behavior of radio and environmental condition, CR must have adaptation ability and to be able to dynamically change the all necessary communication parameters appropriately. A CR senses the spectral environmental conditions over a wide signal frequency band and exploits this signal information to opportunistically deliver wireless links that can best meet the requirement of the user in addition to its radio environments [12]. In this paper,



Fig. 5 Energy detection technique

ED technique has been deployed to develop an improved cognitive radio network under different environmental variation.

#### 3 System Model

ED method was deployed on the measured energy of the accessible radio frequency signal in the communication band of the CR. The result obtained is compared with a predefined threshold level. The predefined threshold value is measured once a noise signal is sensed within the channel only. As soon as all levels of energy drop below the established threshold level ( $E_{th}$ ), the spectrum is registered as available. If the estimated value of energy level is greater than the defined threshold, it is marked as occupied. The purpose of verifying the occupancy status of the PU is to know if the PU is using the spectrum or not at any given time so as to know when the SUs can utilize the spectrum. SUs can only have the available spectrum when the PU is not inactive. The ED technique models the temperature interference to sense the white space. The detected white space will be allocated to unused users based on the RSS of the primary user. The ED technique does not need the prior information of the primary user making it to be less complex when compared with other methods. Figure 6 represents the graph of interference temperature evaluation in (a), an ideal while the plot in (b) is the generalized version.

Considering the PU's power of all the nodes connected, the Gaussian noise is given by:

$$kBT_{L}(f_{c}) (B - B_{i}) + kBT_{N} \sum_{j=1}^{n} B_{j} \le \sum_{j=1}^{n} B_{jpj} \quad \forall 1 \le I \le n$$
(4)

where B stands for the bandwidth and  $T_L$  is the temperature limit.



Fig. 6 Interference temperature evaluation model of an ideal a, and the generalized b

Assuming *p* is the power and it is a function of the bandwidth  $B_{i}$ , then *p* is given by:

$$P \le \min_{i \in [1,n]} [(B_i k / M_h) [T_L(f_i) - T_1(f_i, B_i)]$$
(5)

*i* is the different channels of the spectrum. If the unlicensed signal does not overlap, the spectral density of the derived power is obtained as given in Eq. (6).

$$P \leq \left\{ Bk/M_k \left[ T_L(f_c) \right] \right\} - \left\{ 1/BM_h \left[ \int_{f_c - B/2}^{f_c + B/2} S(f) \, df \right] \right\}$$
(6)

Equation depicts the power of received signal when the temperature limit  $T_L$  and  $M_h$  are considered. The number of times a channel is occupied within a given time period is therefore given by Eq. (7).

Duty Cycle =  $\left[ \text{Signal Occupation period } (n) / \text{Total Observation period } (m) \right] \times 100\%$ (7)

A threshold value better called the decision threshold is endowed with the main feature in evaluating the true spectrum occupancy in the signal frequency band of concern. The energy detection technique of spectrum sensing process compares the value of the received signal of a given frequency band with an established threshold for further decision.

In order to take measurement, SA was used to obtain the RSS of the study area with radial base station (BS) coverage area of 2 km. The experimental data were taken at distances ranging from 100 to 1000 m, within the coverage area of the BS, for three radio paths. The measurements were conducted during the day time. For every route, RSS is measured from a reference distance position of 100 m taking from the base station and a successive interval of 100 m to a distance of 1000 m. The details of the results obtained and their discussion are presented in Sect. 4 of this paper.

#### **4** Results and Discussion

The corresponding RSS against the distance measured from three selected location areas is shown in Fig. 7. RSS was measured from the Frizzlers microwave source, 10–100 m away from the base station. The RSS plot against measured distance from the microwave oven is presented in Fig. 8. Table 1 shows the RSS evaluated from the reference position distance from 100 m up to 1000 m for each of the three routes examined. As can be seen from Table 1, the RSS decreases as the distance from the base station (BS) to mobile station (MS) increases, with the exception of some

measured points along the routes, where the RSS fluctuates owing to environment conditions.

Table 1 shows the measured RSS of the study area. From the results obtained, the spectrum band between 2.409 GH and 2.509 GHz was the least utilized. A noise floor threshold of -60 dBm was observed. By implication, the signal strengths beyond the -60 dbm power are detected and taken as the signal point threshold. This threshold is used to detect white spaces. The 2.40GHZ-2.45 GHz is sparsely empty from the research findings of the studied area when the ED technique with reference to MFD and CFD is deployed.

From the measured values, it is evident that the frequency channel that is the next highly occupied in the 2.4 GHz frequency band is given as channel 11 with the



Fig. 7 RSS versus distance measured from three selected location areas



Fig. 8 RSS versus distance measured from the microwave oven

T-R separation distance (m)	Time (s)	RSS (dBm)		
		i	ii	iii
100	0	-25.00	-30.41	-27.63
200	50	-26.64	-35.52	-39.82
300	100	-28.75	-36.12	-43.25
400	150	-33.26	-40.62	-51.21
500	200	-35.24	-44.93	-57.18
600	250	-40.29	-30.72	-63.10
700	300	-43.27	-50.22	-67.08
800	350	-40.14	-60.33	-70.13
900	400	-52.23	-68.67	-72.10
1000	450	-61.21	-66.31	-73.50

 Table 1
 Received signal strength from the base station at three different locations

frequency of 2.462 GHz. Given in Figs. 9 and 10, respectively, is the spectrogram for mean and max channel occupancy measurements, respectively.

The highest curve points present the highest level of occupancy detected in a given signal channel. The mean points indicate the average occupancy detected in that specific channel within the duration period. Furthermore, the channel mean occupancies present an exciting awareness that channel occupancy levels vary greatly but have an average to greater part of the band to be is free. It can also be seen in the graphical results that there are some WLAN users within the 2400 and the 2470 MHz frequency band. Again, some signals with low power and narrowband whose occupied bandwidth varies between the frequencies of 2 and 3 MHz were equally noticed to belong to a few numbers of systems using audio/video wireless transmission and reception systems. Large number associated with the narrowband activity was detected at  $f_c = 2406$ , 2427 and 2490 MHz, respectively.

From the analysis of the 2.4 GHz frequency band results, it is seen that channel 1, channel 6, and channel 11 are the most utilized. The most utilized is channel 1,



Fig. 9 Spectrogram of mean channel occupancy over the duration



Fig. 10 Spectrogram of max channel occupancy over the duration

followed by channel 11. This means, the least utilized is channel 6 when 2.4 GHz frequency band is considered. Channel 1 of the system is used the most where maximum occupancy level is recorded as 11%. Channel no. 6 is found to be the moderately occupied channel with maximum occupancy level of 7%. Channel 11 was the least occupied channel with maximum occupancy level of 3%. Figure 11 shows the spectrogram for the occupied bandwidth in the location area where signal data were collected. The result depicts that there were no activities going on for most of the periods of the measurements. This was observed from the spectrogram because there were no active wireless access points within the period of the data collection. It is important to note that within these locations, only location with few bands presents some significant activities in the spectrogram. Because of the low occupancies in some locations, the activities on this band were not captured on the spectrogram.

The knowledge of relative bandwidths is that, it may be expected to have a percentage of a channel with a bandwidth B that is above noise threshold at a given time. For instance, for a given 40 MHz IEEE 802.11n channel, a frequency of 33.75 MHz may be used by subcarriers and a 50% relative bandwidth is expected to be



Fig. 11 Spectrogram of the occupied bandwidth

at least 16.86 MHz of the occupied channel above the noise threshold to mark it occupied with full confidence. The occupied bandwidth therefore shows the percentage of the bandwidth that is available relative to the total bandwidth of the frequency band being evaluated.

#### 5 Conclusion

In this study, an investigation of a real-time measurement and analysis of ED spectrum sensing for cognitive radio white space in some selected campus areas of the Federal University of Technology targeting frequency spectrum range between 2.35 and 2.5 GHz has been done. The research is an eye-opener about the available white space cognitive radio spectrum access on the campus to ease the problem of spectrum "scarcity" in the campus area.

#### References

- Chiang RIC, Rowe GB, Sowerby KW (2007) A quantitative analysis of spectral occupancy measurements for cognitive radio. In: IEEE vehicular technology conference, IEEE, Dublin, pp 3016–3020
- 2. Barlemann L, Mangold S (2020) Cognitive radio and dynamic spectrum access, 1st edn. Wiley and Sons, USA
- Mitola J (2021) Cognitive radio architecture in wireless networks: principles and Applications. In: Fitzek FHP, Katz MD (eds) Springer, Dordrecht, pp. 234–311
- 4. Suseela B, Sivakumar D (2018) Certain investigations on effective rate adaptation in cognitive radio with channel characteristics. Int J Netw Virtual Organnization 19(2):373–384
- 5. Ali S, Hamouda W (2016) Advances on spectrum sensing for cognitive radio networks : theory and applications. IEEE Commun Surv Tutorials 5(1):1–29
- 6. Yucek T, Arsian H (2009) A survey of spectrum sensing algorithms for cognitive radio applications. IEEE Commun Surv Tutorials 11(1):116–130
- Wang B, Liu KJR (2016) Advances in cognitive radio networks : a survey. IEEE J Sel Top Signal Process 5(1):1–20
- Eberechukwu PN, Umar DS, Mohd A, Kamaludin MY, Sarijari MA (2018) Interference temperature measurements and spectrum occupancy evaluation in the context of cognitive radio. Indones J Electr Eng Comput Sci 10(3):1007–1012
- 9. Yoo SK et al (2018) Entropy and energy detection-based spectrum sensing over F composite fading channels. IEEE J Sel Areas Commun 16(7):1–30
- Lorincz J, Ramljak I, Begušić D (2019) A review of the noise uncertainty impact on energy detection with different OFDM system designs. Comput Commun 148(10):185–207
- 11. Sofotasios PC, Zhang L, Freear S (2013) Energy detection—based spectrum sensing over  $\kappa \mu$  and  $\kappa \mu$  extreme fading channels. IEEE Trans Veh Technol 62(3):1031–1040
- Zhang I, Xiao M, Wu G, Alam M, Liang Y, Li S (2017) Dynamic spectrum management for 5G: a survey of advanced techniques for spectrum sharing in 5G networks. IEEE Wirel Commun 4(11):44–51