

ABSTRACTS

2025 World Molecular Imaging Congress Program

© The Author(s), under exclusive licence to World Molecular Imaging Society 2026

Selected abstracts from the World Molecular Imaging Congress 2025 meeting of the World Molecular Imaging Society.

WMIC 2025, Anchorage, Alaska, September 29th-October 3rd

Sponsorship: Publication of this supplement was funded by the World Molecular Imaging Society. All content was reviewed and approved by the 2025 WMIC Program Committee, which held full responsibility for the abstract selections. Presenting authors are bolded in the contributor lists.

GA101- Immunomodulatory Photoacoustic Nanoparticle-engineered Macrophages for Solid Cancer Immunotherapy and Longitudinal Monitoring

Seoyoon Song¹, Melissa Cadena¹, Myeongsoo Kim¹, Stanislav Emelianov¹

¹Georgia Institute of Technology, Atlanta, GA

Category: Oncology

Abstract Body:

Background: Reinforcing antitumor functions of macrophages, phagocytosis of cancer cells and secretion of inflammatory cytokines, can be a potent approach to treat solid tumors. Several strategies including CAR-macrophages and phagocytosis-enhanced macrophages (engineered via anti-CD47 antibody treatment) have been recently reported and have shown promise in preclinical models [1, 2]. However, these approaches lack mechanisms for monitoring transferred macrophages and assessing their therapeutic efficacy against tumors, limiting the ability to implement longitudinal therapeutic interventions throughout the treatment. Integrating imaging and contrast agents offers a possibility for real-time and non-invasive tracking of macrophages within the tumor microenvironment. Specifically, labeling macrophages with imaging contrast agents allows for longitudinal visualization of their migration, infiltration, and persistence in tumors, which could serve as an indicator of therapeutic response. Photoacoustic (PA) imaging is a technique that combines ultrasound and optical imaging by leveraging the light-to-sound conversion under laser irradiation of optical absorbers with high-intensity nanosecond laser pulses. PA imaging offers a powerful tool for real-time and noninvasive tracking of adoptively transferred cells. Here, we propose a macrophage engineering strategy for PA image-guided cancer immunotherapy. A nanoparticle formulation with both PA contrast and immunomodulatory effects is synthesized. Macrophages labeled with the formulated nanoparticles demonstrated strong antitumoral phenotypes and allowed longitudinal PA imaging. Our work provides perspectives on engineering macrophages for image-guided cancer immunotherapy.

Methods: Macrophages were derived from murine bone marrow cells. Bone marrow cells were extracted from the femur and the tibia from 5 - 8 weeks old mice. The cells were cultured with 20 ng/mL M-CSF for differentiation into macrophages. The hyperbranched gold nanoconstructs (HBGNCs) were synthesized via surface-blocker assisted seeded growth. Briefly, the surface of 35 nm-sized gold nanospheres was partially blocked during the seeded growth to yield the hyperbranched structure with a construct dimension of 100 nm.

For PA imaging, macrophages were labeled with HBGNCs. Afterwards, cells were washed with PBS and collected. The cell solution was embedded in gelatin phantom. The phantom was submerged in water and imaged under Vevo2100/LAZR imaging system.

The effect of particle labeling on key cellular functions, such as viability, migration, and antitumoral functions (CD80, CD87, MHCII, and CD206 expression), was investigated by confocal microscopy and flow cytometry.

Results: Photostable HBGNCs with high optical absorption efficiency, ~90% in the near-infrared I (NIR I) region, were synthesized. The enhanced optical absorption was attributed to the hyper-branched structure. Due to the enhanced optical responses at NIR I region, the HBGNCs produced robust photoacoustic (PA) responses at corresponding wavelengths, offering high sensitivity in PA imaging. When macrophages were labeled with HBGNCs, the size and the granularity of the cells increased as the particles were internalized. The labeling did not affect the viability of the cells. HBGNC-labeled macrophages embedded in tissue-mimicking phantoms yielded high PA signal.

The migration ability of the labeled macrophages was evaluated. Compared to IFN γ -primed macrophages that are known to migrate at a high rate, macrophages labeled with either HBGNCs or HBGNC-Gs displayed a superior migration ability.

The phenotype of macrophages became more strongly anti-tumoral when labeled with IFN γ -conjugated HBGNCs (HBGNC-Gs) compared to HBGNC and IFN γ alone. This was supported by the increased expression of costimulatory receptors CD80 and CD86, MHCII, and the decreased expression of pro-tumoral marker CD206.

Conclusion: In the current study, a new strategy of macrophage engineering for cancer immunotherapy was introduced. Labeling macrophages with HBGNC-Gs have enabled PA imaging of macrophages and, at the same time, enhanced their migration ability and antitumoral phenotype. Results suggest that HBGNC labeling approach can provide insights into developing strategies for macrophage-based cancer immunotherapy.

Disclosures: The authors have no conflicts of interest to disclose.

References:

1. Klichinsky, M. *et al.* Human chimeric antigen receptor macrophages for cancer immunotherapy. *Nat Biotechnol* **38**, 947–953 (2020)
2. Dooling, L.J. *et al.* Cooperative phagocytosis of solid tumors by macrophages triggers durable anti-tumor responses. *Nat. Biomed. Eng* **7**, 1081–1096 (2023).
3. Kubelick, K.P. *et al.* *In Vivo* Ultrasound and Photoacoustic Imaging of Nanoparticle-Engineered T Cells and Post-Treatment Assessment

Disclosures: The authors have no conflicts of interest to disclose.

References:

1. Narang, S., Lehrer, M., Yang, D., Lee, J., & Rao, A. (2016). Radiomics in glioblastoma: current status, challenges and potential opportunities. *Translational Cancer Research*, 5(4).
2. Zhu, M., Li, S., Kuang, Y., Hill, V. B., Heimberger, A. B., Zhai, L., & Zhai, S. (2022). Artificial intelligence in the radiomic analysis of glioblastomas: A review, taxonomy, and perspective. *Frontiers in oncology*, 12, 924245.
3. Yuan, J., Liu, L., & Hu, Q. (2013). Mathematical modeling of brain glioma growth using modified reaction–diffusion equation on brain MR images. *Computers in biology and medicine*, 43(12), 2007–2013.

Poster Presentation

GA160- Development and Implementation of Physics-Informed Segresnetunet for Brain Tumor Segmentation Using BRATS2020 Dataset

Aniebiet Aaron¹, Michael O. Dada¹, Bamidele O. Awojoyogbe¹, Iniobong N. Udemé¹, Henry Ananyi Sanni¹, Moses A. Iorumbur¹, Emmanuel O. Olasehinde¹

¹Federal University of Technology Minna, Niger State, Nigeria

Category: Computational & Data Science

Abstract Body:

Background: Accurate brain tumor segmentation is crucial for effective diagnosis and treatment planning in brain cancer cases. Traditional segmentation methods often fall short in capturing the complex nature of tumors. This study presents the Physics-InformedResNetUNet model, a deep learning framework that integrates a physics-informed layer simulating realistic tumor growth dynamics into U-Net's segmentation capabilities and ResNet's residual learning. The physics-informed component models the tumor growth using simplified diffusion equations, reflecting how tumors evolve spatially over time, thereby enhancing the network's understanding of tumor morphology.

Methods: Data Preprocessing: For model training, the Physics-Informed ResNetUNet model, preprocessing steps include: Normalization (scaling pixel values to 0–1 for consistency), resizing (standardizing image dimensions to match model input).

Data Augmentation: Techniques like random cropping, flipping, intensity normalization, and random intensity adjustments have been applied to increase data diversity and improve model robustness.

Model Architecture (Physics-Informed ResNetUNet): encoder (uses ResNet-based residual blocks for feature extraction), bottleneck (a deeper residual block captures complex features), decoder (3D transpose convolutions upsample and reconstruct feature maps), dropout (mitigates overfitting). The architecture is illustrated in figure 1.

Physics-Informed Layers: simulates tumor growth using an anisotropic diffusion equation, factoring in oxygen levels and necrosis.

Training Process: this includes batch processing, Dice loss calculation, and gradient updates. Physics-informed inputs simulate tumor growth to guide segmentation predictions.

Validation: Evaluated post-epoch with Dice scores for different tumor regions (core, whole tumor, enhancing tumor), and the best model was saved based on their performance. Key metrics tracked were learning rate adjustments, training and validation loss, and Dice scores according to tumor region.

Results: Over the last five epochs, the Physics-Informed ResNetUNet achieved the following scores: Mean Dice of 0.6975, TC Dice of 0.6763, WT Dice of 0.7180, ET Dice of 0.6983, and a training loss of 0.3420 with an average time of 52.44 seconds per epoch. In

comparison, SegResNet recorded a Mean Dice of 0.4150, TC Dice of 0.6608, WT Dice of 0.5689, ET Dice of 0.0154, and a training loss of 0.8876 with an average time of 81.53 seconds per epoch. Finally, U-Net achieved Mean Dice of 0.0511, TC Dice of 0.0197, WT Dice of 0.1133, ET Dice of 0.0204, and a training loss of 0.9418 with an average time of 41.36 seconds per epoch. Table 1 shows the performance of ResNetUNet and SegResNet in comparison with traditional UNet. Figure 2 shows the performance of the model on training and testing dataset showing the segmented tumor region.

Conclusion: The results demonstrate that the Physics-Informed ResNetUNet outperformed both SegResNet and U-Net in segmentation accuracy, particularly for the Whole Tumor and Enhancing Tumor regions. The incorporation of tumor growth dynamics as an additional layer allows the model to better reflect the physical processes underlying tumor development, leading to a more reliable and precise tool for clinical applications in brain tumor segmentation.

Disclosures: The authors have no conflicts of interest to disclose.

References:

1. Harris, C. R., Millman, K. J., van der Walt, S. J., Gommers, R., Virtanen, P., Cournapeau, D., Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., van Kerkwijk, M. H., Brett, M., Haldane, A., Del Río, J. F., Wiebe, M., & Oliphant, T. E. (2021). Array programming with NumPy. *Nature*, 585(7825), 357–362.
2. Ioffe, S., & Szegedy, C. (2015). Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International Conference on Machine Learning (ICML)* (pp. 448–456). <https://proceedings.mlr.press/v37/loff15.html>
3. Kingma, D. P., & Ba, J. (2014). Adam: A method for stochastic optimization. *arXiv Preprint, arXiv:1412.6980*.
4. Menze, B. H., Jakab, A., Bauer, S., Kalpathy-Cramer, J., Farahani, K., Kirby, J., Burren, Y., Porz, N., Slotboom, J., Wiest, R., Handels, H., & van Leemput, K. (2015). The multimodal brain tumor image segmentation benchmark (BRATS). *IEEE Transactions on Medical Imaging*, 34(10), 1993–2024.
5. Micikevicius, P., Narang, S., Alben, J., Diamos, G., Elsen, E., Garcia, D., Ginsburg, B., Houston, M., Kuchaiev, O., Venkatesh, G., & Shoenybi, M. (2018). Mixed precision training. *arXiv Preprint, arXiv:1710.03740*.

Poster Presentation

GA161- Physics-informed UNETR: A Brain Tumor Segmentation Combining UNETR Architecture and Physics Constraints Using Brats2021 Dataset and Insights for Molecular Imaging

Michael O. Dada¹, Bamidele O. Awojoyogbe¹, Samuel O. Lawal¹, Iniobong N. Udemé¹, Henry Ananyi Sanni¹, Emmanuel O. Olasehinde¹, Moses A. Iorumbur¹, Oluwatobi Akinyemi¹

¹Federal University of Technology Minna, Niger State, Nigeria

Category: Computational & Data Science

Abstract Body:

Background: This Physics-Informed UNETR model incorporates both learned features from MRI scans and the physical constraints of tumor dynamics, offering a more holistic and accurate segmentation. By integrating reaction-diffusion equations, which govern tumor expansion, the model aims to provide more accurate segmentation results, especially in complex cases with irregular tumor boundaries. The problem, therefore, lies in how to effectively combine state-of-the-art deep learning techniques with well-established biological models to improve the accuracy and reliability of brain tumor segmentation. This study seeks to address this gap by developing a novel approach that leverages both